

CONIROOF

Roofing Systems

Spray applied membrane

System 2102	Products	Consumption
Primer	Please consult our technical service, according to substrate	
Membrane	M 802 FL	
Topcoats	TC 458 TC 459 TC 463HE TC 464HE	0.3-0.4kg/m ² 0.25-0.35kg/m ² 0.15-0.20kg/m ² 0.35kg/m ² /coat

This system has been tested to provide an FAA or SAA fire rating in accordance with BS476 Pt3: 1958 and can therefore be used on any roofing applications where the membrane is to be left exposed, such as insulated/warm roofs, overlays or original roof waterproofing and profiled sheeting re-waterproofing. BBA approved and assessed to be durable for a 'minimum of 25 years'.

System 2110		
Primer	Please consult our technical service, according to substrate	
Membrane	M 800	
Topcoats	TC 458 TC 459 TC 463HE TC 464HE	0.3-0.4kg/m ² 0.25-0.35kg/m ² 0.15-0.20kg/m ² 0.35kg/m ² /coat

CONIROOF 2110 system has been used since 1985 to waterproof all types of flat or pitched roofs. Extensively used in buried membrane applications such as inverted (upside down) roofs, roof gardens and landscaped areas. BBA approved and assessed to be durable for 'the life of the structure' that it is applied to.

System 2111		
Primer	Please consult our technical service, according to substrate	
Membrane	M 810	
Topcoats	TC 458 TC 459 TC 463HE TC 464HE	0.3-0.4kg/m ² 0.25-0.35kg/m ² 0.15-0.20kg/m ² 0.35kg/m ² /coat

Suitable for all types of roofing applications and ideal for buried membrane applications.

System 2160		
Primer	Please consult our technical service, according to substrate	
Membrane	M 865Z	
Topcoats	TC 458 TC 459 TC 463HE TC 464HE	0.3-0.4kg/m ² 0.25-0.35kg/m ² 0.15-0.20kg/m ² 0.35kg/m ² /coat

BBA approved system where the membrane is applied using rollers, brush and squeegee.
Predominately used in buried membrane applications or where no fire performance is determined.

Balconies and walkways

Spray applied membrane

System 2112		
Primer	P660	
Membrane	M800 or M810	
Wear Coat	WC880	
Topcoats	TC480 TC481	

Fast curing anti-slip balcony system provides a decorative, slip-resistant surface for foot or vehicular traffic. This allows the application of the full system to be completed and open to use within 24 hours.

Hand applied membrane

System 2161		
Primer	P660	
Membrane	M865Z	
Wear Coat	WC880	
Topcoats	TC480 TC481	

Similar to 2112 Spray System but uses the waterproof membrane applied using brushes and rollers. Keeps disruption to residing occupants of buildings to a minimum leaving no VOC containing elements in its make up.